

EXOFIT NEX™ ARC FLASH HARNESS

- Nomex®/Kevlar® fibre shoulder, back and leg comfort padding
- Tech-Lite™ stand-up PVC-coated aluminum back D-ring
- Duo-Lok™ quick-connect chest and leg straps
- Leather insulators
- Nomex®/Kevlar® fibre webbing
- Belt loops
- Built-in lanyard keepers
- Revolver™ vertical torso adjusters
- Impact Indicator
- Integrated flame-resistant trauma straps
- Built-in reflective materials
- Protected labels, equipped with i-Safe™
- Type: Fall Arrest, Multi-Purpose
- Weight Capacity: 420 lbs.
- D-Rings: Back
- Leg Strap Connections: Quick-Connect
- Chest Strap Connections: Quick-Connect



Fall Protection



Model No.	Mfg. No.	CSA Class	Size	Price /Each
SEP865	1103087C	A	Large	

SHOCKWAVE™ 2 LANYARDS

- Tubular core style lanyards uniquely designed to expand and contract in reaction to a workers movements
- Stays out of your way when not in use, avoiding trips and snags
- Built in impact indicator provides visual evidence if the lanyard has been involved in a fall
- Elastic Nomex®/Kevlar® fiber webbing and snap hooks at each end
- Arc flash rated
- Length, Type: 6', Shock-Absorbing
- CSA Minimum Mass: 133 lbs.
- CSA Maximum Mass: 253 lbs.
- Harness Connection: Snap Hook
- Anchorage Connection: Snap Hook
- Material: Kevlar, Nomex®
- Shock Absorber Type: Tubular Core
- No. of Legs: 1
- Certification(s): CSA Standard Z259.11

Model No. SEP841
Mfg. No. 1244610C
Price/Each \$



Fall Protection

SHOCKWAVE™ 2 ARC FLASH WEB LOOP SHOCK ABSORBING LANYARD

- Stretches in reaction to your movements
- User friendly self locking snap hook at one end
- Web loop choker
- Energy absorbing design limits fall arrest forces
- Built-in impact indicator
- Protected labels, equipped with 3M™ Connected Safety ID (CSID)
- Length: 6'
- CSA Minimum Mass: 132 lbs.
- CSA Maximum Mass: 253 lbs.
- Harness Connection: Choke-Off Loop
- Anchorage Connection: Snap Hook
- Material: Kevlar®, Nomex®
- Shock Absorber Type: Tubular Core
- No. of Legs: 1

Model No. SES815
Mfg. No. 1244611C
Price/Each \$



Fall Protection

NON-CONDUCTIVE CORRUGATED SWITCHBOARD NO. 702 & DIAMOND PLATE SWITCHBOARD NO. 701

CAN INSULATE UP TO 30 000 V!

- High-performance non-conductive matting protects personnel in areas with dangerous high-voltage equipment
- Maximum rating: 30 000 V
- Recommended usage: up to 17 000 V
- The corrugated surface is abrasion resistant and easily cleaned
- 1/4" thick
- Conforms to ANSI/ASTM D-178-01 Type 2, Class II
- Passes MSHA IC-246 fire resistance test (mining safety)
- Colour: Black

1-YEAR WARRANTY



NO. 702

Model No.	Dim.			Price /Each
	W'	x	L'	
CORRUGATED				
SAL242	2	x	75	
NB657	3	x	75	

NO. 701

Model No.	Dim.			Price /Each
	W'	x	L'	
DIAMOND-PLATE				
SAL236	2	x	75	
SAL238	3	x	75	