

LANDSCAPING & OUTDOOR EQUIPMENT



CLEANING & RESTORATION SERIES HANDHELD MISTER

- Features Viton® seals for maximum durability
- Integrated graduated fill marks
- Ergonomic handle design for maximum comfort
- Weighted dip tube allows spraying at various angles
- Includes: High foam nozzle, Poly adjustable nozzle



Model No.	Mfg. No.	Tank Capacity	Price /Each
N0284	190455	50 oz. (1.5L)	

INDUSTRIAL & CONTRACTOR SERIES H₂O WATER SUPPLY TANK

- Water supply tank provides water for dust suppression during concrete sawing and coring applications to help users become OSHA compliant
- Kink resistant 10' helix coil hose and quick connect to adapt to core drilling, cut-off, and flat saws
- Low center of gravity tank with hose clip strap to prevent tipping during use
- Dip tube filter and dust-blocking pump cap to prevent clogging during use
- Tank Capacity: 3 gal. (13.5 L)
- Tank Material: Polyethylene
- Hose Length: 10"
- Wand Material: Brass



Model No.	Mfg. No.	Description	Price /Each
N0278	190552	Industrial & Contractor Series H ₂ O Water Supply Tank	

SPARE PARTS

N0312	183821	10' Helix Coil Hose	
N0347	183820	Quick Connect	

PEST CONTROL SERIES PROFESSIONAL ELECTRIC THERMAL FOGGER

- Utilizes a 110V power supply
- Heats in minutes for hours of use
- Eliminates pests for up to 6 hours
- Durable aluminum solution tank
- Removable heating element for electric spraying capabilities
- Temperature controlled fog capability
- Heating element atomizes chemical into fine particles that float under surfaces and into nooks and crannies
- For thermal fogging only, use products formulated specifically for thermal fogging such as oil or water-based solutions containing propylene glycol oils



Model No.	Mfg. No.	Tank Capacity	Price /Each
N0294	190443	1 gal.	

S100 PEST CONTROL COMPRESSION SPRAYER

- AISI-304 grade stainless steel tank with wide mouth opening built to withstand harsh chemicals along with rugged transport and use
- Stainless steel wand containing a no-drip valve stem with integrated filter
- Viton® seals, gaskets and check-valves through the pump and shut-off
- Pull button pressure release valve safely releases internal pressure prior to opening the tank
- Gauge monitors pressure where PSI is critical for consistent and even application of chemicals
- 4-way multi-jet nozzle has fine fan, coarse fan, pin, plus crack and crevice options
- Tank Material: Stainless Steel



Model No.	Mfg. No.	Tank Capacity	Hose Length"	Wand Length"	Price /Each
N0288	190441	1 gal. (4.5 L)	50	12	

VICTORY ELECTROSTATIC HANDHELD SPRAYER

- Allows you to spray your surfaces for hours at a time without the hassle of dragging a cord
- Designed to save time and labour, spray less liquid, and cover more surfaces
- Provides an electrical charge to solutions, allowing them to wrap conductive surfaces with an effective and even coverage
- Double-charged particles envelope all surfaces whether they're shadowed, vertical or underneath
- Standard 3-in-1 nozzle allows the user to match the particle's size to the chemical's required dwell time
- Voltage: 16.8 V
- Optimum Spray Range: 2' - 3'
- Coverage Per Single
- Tank: 1700 - 2800 sq. ft.
- Weight: 5.9 lbs. (full tank)
- Nozzle Spray Sizes: 40 Micron (full cone), 80 Micron (full cone), 110 Micron (120° fan)



Model No.	Mfg. No.	Description	Tank Capacity	Price /Each
JM081	72000	Sprayer	1 L	
SPARE PARTS				
JN478	72012	Tank with Cap, 16.8 V Voltage	-	
JN477	72011	Battery Charger, 16.8 V Voltage	-	
JN475	72010	Rechargeable Battery, Lithium-Ion, Run Time 8 hrs.	-	
JN476	72010A	Rechargeable Battery, Lithium-Ion, Run Time 4 hrs.	-	

VICTORY ELECTROSTATIC BACKPACK SPRAYER

- Allows you to spray your surfaces for hours at a time without the hassle of dragging a cord
- Designed to save time and labour, spray less liquid, and cover more surfaces
- Provides an electrical charge to solutions, allowing them to wrap conductive surfaces with an effective and even coverage
- Double-charged particles envelope all surfaces whether they're shadowed, vertical or underneath
- Standard 3-in-1 nozzle allows the user to match the particle's size to the chemical's required dwell time
- Voltage: 16.8 V
- Optimum Spray Range: 4' - 6'
- Coverage per singletank: 23,000 sq. ft.
- Weight: 10 lbs. (empty tank), 29 lbs. (full tank)
- Nozzle Spray Sizes: 40 Micron (full cone), 80 Micron (full cone), 110 Micron (120° fan)
- Run Time: 4 Hours per charge
- Charge Time: 90 min.



Model No.	Mfg. No.	Description	Tank Capacity	Price /Each
JM082	72001	Sprayer with battery & charger	8.5 L	
SPARE PARTS				
JN479	72013	Tank with Cap	-	
JN477	72011	Battery Charger, 16.8 V Voltage	-	
JN475	72010	Rechargeable Battery, Lithium-Ion, Run Time 8 hrs.	-	
JN476	72010A	Rechargeable Battery, Lithium-Ion, Run Time 4 hrs.	-	